



**MODUCLEAN**  
**SLIDING DOORS**

## Description

Single or double leaves thickness 40mm. Airproof assembly. Monobloc doorframe. Air-tightness with static sealant EPDM on 4 sides. Made of lacquered paint on epoxy steel sheet or stainless steel 304.

View panel in single or double leaves thickness 40mm. Rockwool core.

An optimal sliding characteristic due to the coordinated profile of the roller and track makes it the best fit for high-frequented areas. Standard single leaf is 1200mm x 2100mm, double is 2400mm x 2100mm.

## Products advantages

Reinforced air-tightness door for clean room.

Substantial self-cleaning roller carriage technology for durable and long life sliding movement.

User and maintenance-friendly by safe diagnosis due the new developed mechanical features.

Attractive design

## Mechanical and electrical options:

Integral monobloc door frame, Stainless steel protections at the bottom of the door, Emergency stop button, Magic switch, Reader card, Flush access control lights boards, Interlocking with programmable logic controller. Power-drive is a modern automatic linear sliding door for use in interior or external areas. The powerful drive is made for heavy weight doors, single and double doors with metal framework leaf.

The power-drive is also equipped to be use in case of emergencies and always offers the highest degree of security. In additional, the FR variation with redundant 2 motor technologies will never let you down, even in the case of emergencies. The power-drive sliding door system is certified according to DIN 18650.

